

Material Safety Data Sheet

PURITAN NEUTRAL FLOOR CLEANER

PURITAN NEUTRAL FLOOR CLEANER

Page: 2/4

Special protective equipment : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 1. Chemical product and company identification

Trade name : PURITAN NEUTRAL FLOOR CLEANER
Product use : Floor Cleaner
Supplier : Puritan Services Inc.
655 Lone Oak Drive
Eagan MN 55121
1-800-275-8914
992297-01
Code :
Date of issue : 23-March-2006

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	% by weight
benzenesulfonic acid, dodecyl-, compd. with 2,2',2''-nitriothethanol	27323-41-7	4
propan-2-ol	67-63-0	1

Section 3. Hazards identification

Physical state : Liquid. (Liquid.)
Emergency overview : CAUTION!

COMBUSTIBLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FIRE.

Repeated or prolonged contact with irritants may cause dermatitis.
MAY CAUSE EYE IRRITATION.

Avoid contact with eyes. Keep away from heat, sparks and flame. Keep container closed.
Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Slightly irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : Slightly irritating to the respiratory system.
Ingestion : No known significant effects or critical hazards.
See toxicological information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses and flush again. Get medical attention if irritation occurs.
Skin contact : Wash with soap and water. Get medical attention if irritation develops. Wash clothing before reuse.
Inhalation : If irritation persists, get medical attention.
Ingestion : Do not induce vomiting. Never give anything by mouth to an unconscious person. If irritation persists, get medical attention.

Section 5. Fire fighting measures

Flash point : 54.4444 °C (Closed cup)
Product does not support combustion.
Fire-fighting media and instructions : In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Dike area of fire to prevent runoff.
Combustible liquid and vapor. May burn, but does not ignite readily. Under high temperatures or under moderate heating might release vapor in sufficient quantities to produce hazardous atmospheres with air.

Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.
Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for cleaning up : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling : Keep away from heat, sparks and flame. To avoid fire, eliminate ignition sources. Wash thoroughly after handling.
Storage : Keep out of the reach of children. Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Do not store above -10°C

Section 8. Exposure controls, personal protection

Engineering controls : Good general ventilation should be sufficient to control airborne levels.

Personal protection

Eyes : No protective equipment is needed under normal use conditions.
Hands : No protective equipment is needed under normal use conditions.
Skin : No protective equipment is needed under normal use conditions.
Respiratory : No protective equipment is needed under normal use conditions.

Exposure limits

ACGIH TLV (United States, 1/2004).
STEL: 400 ppm 15 minute/minutes. Form: All forms
TWA: 200 ppm 8 hour(s). Form: All forms
OSHA PEL (United States, 8/1997).
TWA: 980 mg/m³ 8 hour(s). Form: All forms
TWA: 400 ppm 8 hour(s). Form: All forms

Section 9. Physical and chemical properties

Physical state : Liquid. (Liquid.)
Color : Orange.
Odor : citrus
pH : 7 (100%)
Boiling/condensation point : 100 °C
Specific gravity : 1.004 (Water = 1)
Dispersibility properties : Easily dispersed in cold water, hot water.
Solubility : Easily soluble in cold water, hot water.

Item # 790002

Responsible name : Regulatory Affairs
 Date of previous issue : No previous validation.
 Notice to reader
 The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.

Section 10. Stability and reactivity

Stability : The product is stable.
 Reactivity : Slightly reactive to reactive with acids.

Section 11. Toxicological information

Potential acute health effects
 Eyes : Slightly irritating to the eyes.
 Skin : Slightly irritating to the skin.
 Inhalation : Slightly irritating to the respiratory system.
 Ingestion : No known significant effects or critical hazards.
 Chronic effects on humans : Contains material which causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological information

Products of degradation : These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ etc.), sulfur oxides (SO₂, SO₃ etc.).

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	Not regulated				

APPLIES ONLY DURING ROAD TRANSPORT
 Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification : Combustible liquid
 Target organ effects : None
 U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: None.
 : SARA 302/304 emergency planning and notification: None.
 TSCA 8(b) inventory : All materials are listed or exempt.
 SARA 313 : Product name
 Form R - Reporting requirements: propan-2-ol
 California Prop. 65 : No products were found.
 Concentration : 1.001

Section 16. Other information

Hazardous Material Information System (U.S.A.) :

Health	1
Fire hazard	2
Reactivity	0
Personal protection	-

Date of issue : 23-March-2006.